SIGNATURE SERIES
QUOTE REQUEST FORM

DATE:	
DEALER:	
ADDRESS:	
BUYING GROUP:	☐ NONE ☐ NAFED ☐ IFED ☐ STRATA
REQUESTOR:	
PHONE #:	
EMAIL:	
JOB NAME:	
JOB LOCATION:	
DELIVERY TO ZIP:	☐ CUSTOMER ARRANGE FREIGHT
SALES REP:	
EMAIL:	

APPLICATION TYPE: ☐ INDOOR ☐ OUTDOOR
BOX TYPE: ☐ COOLER ☐ FREEZER ☐ COMBO

PROVIDE A SKETCH:

INSULATION THICKNESS: ☐ 4" (STD) ☐ 5-3/8"
FOAM-IN-PLACE FLOOR: ☐ YES ☐ NO ☐ FREEZER ONLY

INTERIOR FLOOR FINISH:
☐ SMOOTH ALUMINUM ☐ ALUMINUM DIAMOND TREADPLATE
☐ OTHER: _____

FLOOR TYPE:
☐ STANDARD (1,200 LBS PER SQ FT)
☐ HEAVY DUTY (1,500 LBS PER SQ FT) *TYPICAL FOR KEGS
☐ PALLET JACK (2,600 LBS PER SQ FT)
☐ OTHER _____

SPECIAL BUILDING REQUIREMENTS:
☐ ANCHORING PROVISIONS
☐ SEISMIC CALCULATIONS (REQUIRES ANCHORING PROVISIONS)

PANEL FINISHES (STUCCO EMBOSSED):

INTERIOR WALL FINISH	☐ STANDARD	☐ WHITE
CEILING INTERIOR	☐ STANDARD	☐ WHITE
EXPOSED EXTERIOR	☐ STANDARD	☐ WHITE
UNEXPOSED EXTERIOR	☐ STANDARD	☐ WHITE
DOOR FINISH	☐ STANDARD	☐ WHITE

OTHER: _____

SWING DOORS:
☐ 30" X 78"
☐ 34" X 78" (STD)
☐ 36" X 78"
☐ 42" X 78"
☐ 48" X 78"
☐ OTHER: _____

SLIDING DOORS:

☐ 36" X 78"	☐ MANUAL	☐ ELECTRIC
☐ 42" X 78"	☐ MANUAL	☐ ELECTRIC
☐ 48" X 78"	☐ MANUAL	☐ ELECTRIC
☐ 60" X 78"	☐ MANUAL	☐ ELECTRIC
☐ 72" X 78"	☐ MANUAL	☐ ELECTRIC

DOOR ACCESSORIES:
** STANDARD DOORS ARE EQUIPPED WITH BRUSHED CHROMED HANDLE WITH KEYLOCK, 36"H INT/EXT DIAMOND TREAD KICKPLATES, LIGHT SWITCH/THERMOMETER, VAPOR PROOF LED LIGHT, DOOR CLOSER, (2) CAM LIFT HINGES, ELECTRICAL CONDUIT, AND SAFETY NIGHT LIGHT.

☐ STRIP CURTAIN ☐ 3RD CAM LIFT HINGE
☐ 14" x 14" VIEW PORT ☐ 14" x 24" VIEW PORT

DISPLAY GLASS DOORS:
GLASS DOOR WIDTH ☐ 24" ☐ 26" ☐ 28" ☐ 30"
GLASS DOOR HEIGHT ☐ 67" ☐ 75" ☐ 79"
GLASS DOOR QUANTITY _____
HINGE DIRECTION ☐ LEFT ☐ RIGHT
SHELVING SIZE ☐ 24" DEEP ☐ 27" DEEP ☐ 36" DEEP
SHELVING TYPE ☐ FLAT SHELVING ☐ GRAVITY FEED
NO. OF SHELVING TIERS ☐ 5 ☐ 6 ☐ 7
FINISH ☐ SILVER ☐ BLACK
IF DOOR BY OTHERS, SPECIFY REQUIRED FRAMED OPENING:
_____

BOX ACCESSORIES:
☐ INTERIOR RAMP ☐ EXTERIOR RAMP ☐ METAL COVE BASE (CALIFORNIA)
☐ CLOSURE PANEL ☐ TRIM STRIPS ☐ LED LIGHTS ☐ NON-SKID STRIPS
☐ MASS INSULATION & VISQUEEN (FLOORLESS FREEZERS)
☐ SLOPING MATERIAL (MEMBRANE INCLUDED) ☐ MEMBRANE ONLY
☐ RAIN GUTTER (OVER DOOR)

REFRIGERATION: ☐ INDOOR ☐ OUTDOOR ☐ COMPRESSOR STAND ☐ REMOTE PRE-ASSEMBLED ☐ SELF-CONTAINED

VOLTAGE: ☐ 208/230/1 ☐ 208/230/3 ☐ 460/3
COOLER HOLDING TEMP: _____ °F **FREEZER HOLDING TEMP:** _____ °F
☐ FREEZER OPENING INTO A COOLER ☐ BEER IN COOLER

** STANDARD REFRIGERATION SYSTEMS ARE ENGINEERED FOR HOLDING TEMPERATURE ONLY AND 2 DOOR OPENINGS PER HOUR. HEAVY PRODUCT LOAD WITH HIGHER ENTERING TEMPRATURES IS NOT FACTORED INTO REFRIGERATION SIZING OR PULL-DOWN TARGETS. FOR SPECIAL CONDITIONS/REQUIREMENTS, PLEASE SPECIFY.

COMMENTS:

9731 NW 114TH Way | Miami, FL 33178 | 305-883-5581
1340 W. Gladstone St | Azusa, CA 91702 | 626-508-0920
sales@arcticwalkins.com